

**JACOBSEN**

Utility Vehicle

# TRUCKSTER™ LS/LX



**TRUCKSTER™ LX** (Base)  
model shown with options.

**AMPED UP AND READY TO WORK AS HARD AS YOU DO.**

## **NO MORE PUSHING UP THOSE BIG HILLS**

- Available lifted suspension allows the Truckster LX to handle rough terrain with ease.
- Polyethylene bed won't rust or wear out providing years of worry-free service.
- Compact design and up to 800 lb. vehicle capacity is the perfect combination for whatever task at hand.



**TRUCKSTER™ LS** (Base)  
model shown with options.

## **QUICK SPECS**

**Engine:** 13 hp (9.7 kW)

**Capacity:**

**LS** 800 lb (363 kg)

**LX** 800 lb (363 kg)

**Drive Train:**

Auto: Continuously Variable (CVT)

**Speed:**

**LS** 17 mph (27.4 kph)

**LX** 17 mph (27.4 kph)

**Dimensions:**

**LS** Length 107 in (2.72 m)

Width 49.5 in (1.26 m)

**LX** Length 107 in (2.72 m)

Width 48.5 in (1.23 m)

### SPECIFICATIONS

	TRUCKSTER LS	TRUCKSTER LX
<b>Engine</b>	<b>Gas</b>	
Type	13 hp (9.7 kW) Exceeds SAE J1940 Standard, 4 cycle, 24.5 ci (401 cc) single cylinder, air-cooled Kawasaki	
Air Cleaner	Replaceable dry cartridge	
Fuel Capacity	6.0 gallon (22.7 L) tank	
Electrical System	Starter/Generator. Solid State Regulator	
<b>Drive Train</b>		
Transmission	Continuously variable transmission (CVT) Transaxle Differential with Helical Gears	
Speeds	17 mph +/- 0.5 mph (27.4 kph +/- 0.8 kph)	
<b>Tires, Brakes and Steering</b>		
Brakes	Service Brake: Real wheel mechanical self-adjusting drum Parking Brake: Self-compensating, single point engagement	
Steering	Self-compensating Rack & Pinion	
Front Suspension	Leaf springs with hydraulic shock absorbers	
Rear Suspension	Leaf springs with hydraulic shock absorbers	
<b>Weight and Dimensions</b>		
Maximum Capacity	800 lb (363 kg)	800 lb (363 kg)
Bed Capacity	500 lbs (227 kg)	400 lbs (181 kg)
Ground Clearance	4.3 in (11 cm)	4.3 in (11 cm)
Weight	Dry Weight: 750 lbs (340 kg)	Dry Weight: 810 lbs (367 kg)
Length	107 in. (2.72 m)	
Height		
With Canopy:	70 in. (1.78 m)	71.5 in. (1.82 m)
Without Canopy	46.5 in (1.18 m)	49.0 in (1.24 m)
Wheelbase	65.5 in. (1.66 m)	
Width	49.5 in. (1.26 m)	48.5 in. (1.23 m)
Bed	5.9 cu ft (0.17 m <sup>3</sup> ) Polyethylene	

\*Engine horsepower is provided by engine manufacturer. Actual operating power output may vary due to conditions of specific use.

NOTE: Specifications, while correct at time of printing, may change without notice.

### PRODUCT CONFIGURATION

S = Standard D = Dealer Install

	LS	LS	LX
	Base	Premium	Base
<b>Tires &amp; Wheels</b>			
<b>Front</b>			
Links 18 x 8.50 - 8 (4 Ply Rated)	S	S	
Turf Saver 20 x 10.0 - 10			S
<b>Rear</b>			
Turf Saver 20 x 10.0 - 10	S	S	S
<b>Other Enhancements</b>			
Brush guard	S	S	S
<b>Electrical</b>			
12 Volt Outlet		S	
Hour Meter	S	S	S
Headlights	S	S	S
LED Headlights	D	D	D
Taillights		S	
Brake Lights		S	
Turn Signals with 4-Way Flashers		D	
Fuel Gauge with oil light	S	S	S
<b>Hauling &amp; Towing</b>			
2 in (5 cm) Receiver (Rear)	D	S	S
<b>Weather Protection</b>			
Sun Canopy (Top) Black	D	D	D
Weather Enclosure (3 Side, Top & Windshield Req'd)	D	D	D
Windshield Split Kit	D	D	D
<b>Vehicle Cab</b>			
Steel Cab without doors (White)	D	D	
Doors (Steel) White (Cab Required)	D	D	
Mirrors (Cab Required)	D	D	
Strobe Light (Cab Required)	D	D	
Switch Panel (Cab Required)	D	D	
Windshield Wiper (Cab Required)	D	D	
Work Light (Cab Required)	D	D	